

Declaration of Performance

No DOP: 0432-CPR-00095-310



1. Unique identification code of the product types:

**Air-flue chimney system made of stainless steel
System MKPS according to EN 14989-2: 2007 and EN 1856-1: 2009**

2. Identification of the construction product, in accordance with Article 11 § 4:

System MKPS

Version 1	T200 – P1 – W – V2 – L50050 – O00
Version 2	T200 – P1 – W – V2 – L99050 – O00
Version 3	T200 – P1 – W – Vm – L20050 – O00
Version 4	T200 – P1 – W – V2 – L99040 – O00
Version 5	T200 – P1 – W – Vm – L20040 – O00

3. Use or intended use of the construction product in accordance with the relevant harmonized technical specification as provided by the manufacturer:

Evacuation of combustion products from the furnace to the outside atmosphere

4. Name, company name or trademark and contact address of the manufacturer, in accordance with Article 11 § 5:

MK Sp. z o.o.

ul. Wiśniowa 24

PL 68-200 Żary

Tel: +48684581919; Fax: +48684581914

e-mail: sekretariat@mkzary.pl

5. Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 §2:

not applicable

6. The system or systems of assessment and verification of constancy of performance of construction product in accordance with Annex V:

System 2+ and System 4

7. Notified body certifying the factory production control **No 0432**



**Materialprüfungsamt Nordrhein-Westfalen
Marsbruchstraße 186; D-44287 Dortmund**

has carried the initial inspection of the factory and control of factory production and performs the continuous surveillance, assessment and approval of factory production control and on the 15.07.2015 has issued the compliance certificates **No 0432-CPR-00095-310** for the factory production control.

8. **Declared performance in accordance with EN 14989-2:2007, EN 1856-1:2009, annex ZA**


Essential characteristics	Performance	Comments
Materials and sheet thicknesses		
Inner pipe	Version 1 1.4404; 1.4571 from 0,5 mm (minimum 0,45 mm) Version 2 1.4521 from 0,5 mm (minimum 0,45 mm) Version 3 1.4301 from 0,5 mm (minimum 0,45 mm) Version 4 1.4521 0,4 mm (minimum 0,36 mm) Version 5 1.4301 0,4 mm (minimum 0,36 mm)	The range of nominal diameters DN: (60-100) to (350-500)
Outer pipe	Version 1 - 3 1.4509, 1.4301 from 0,5 mm (minimum 0,45 mm) Version 4 and 5 1.4509, 1.4301 from 0,4 mm (minimum 0,36 mm) Painted or not painted surface.	
Sealing	Seals according to EN 14241-1	
Thermal insulation	Air	
Mechanical strength		
Compressive strength Segments of the chimney, fittings and supports	Version 1 - 5 DN (60-100) – (350-500): to 20 m	For more information, see the manual
Non-vertical installation	Version 1 - 5 3 m at 45°	The maximum distance between two supports
Wind load resistance	Version 1 - 5 DN (60-100) – (350-500): 4 m	The maximum distance between the two side fixings
	DN (80-100) – (350-500): 3 m	Free end above the last clamping
Working conditions		
Fire resistance	Version 1 - 5 to T200 – O00	Tested in fully ventilated floor penetrations
Tightness	P1	Working in positive pressure
Flow resistance Fittings and terminals; roughness	According to EN 13384-1; R = 1 mm	Normative value: see the method of calculation
Thermal resistance	0 m ² K/W	Specified at 200 °C
Resistance to thermal shock		
Heat load at nominal temperature	T200	Test temperature 250° C
Sootfire resistance	Not (designation O)	Test temperature 250° C
Durability		
Water vapor diffusion and water resistance	Yes	
Condensate penetration resistance	Yes	

Corrosion resistance	Version 1, 2, 4: V2	For gas, fuel oil and wood (open furnace)
	Version 3, 5: Vm	For gas
Freeze-thaw resistance	Yes	
Additional information		
Carrying away of condensate	(D) M251 instruction of Sewage Disposal Methods Association	Necessary neutralization of sewage
Storage conditions	Do not store in corrosive environment	
Methods of cleaning	Do not use the tools of black steel	
Position of cleaning openings	(D): According to DIN 18 160	Observe the national regulations
Identification of flue systems	(D): According to DIN 18 160 Durable plate, mounted on installation, housing or casing	Observe the national regulations
Protection against contact	Chimney doesn't require any additional safety precautions; the maximum temperature for the surface of the chimney at the T200 <70° C	
Direction of flow	Core pipe female socket upwards	
Installation and assembly	Follow the instructions	

9. The performance of the product identified in points 1 and 2 is consistent with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer mentioned in point 4.

On behalf of the manufacturer signed:


Kinga Pachnik – Managing Director


Ireneusz Koman – Plant Director

Żary 01-09-2015